

Stepan Alkoxylate Product Guide

Stepan Trade Name	Chemical Description	Average # of Moles EO	Molecular Weight	Appearance at 25°C	HLB	Activity, %	Density at 25°C, U.S. lbs/gal	Pour Point, °C	Cloud Point, °C	Surface Tension, dynes/cm % Deionized (DI) Water			Draves Wetting Test, seconds 0.1% in DI Water	Ross Miles Foam Test, cm 0.1% in DI Water	
										0.10%	0.01%	0.001%		Initial	5 minutes
Linear Alcohol Ethoxylates															
BIO-SOFT® N91-2.5	C9-11 Alcohol ethoxylate	2.5	281	Liquid	8.5	99.5 min.	7.71	-10	<0 ¹	25.7	26.3	45.0	7	1.0	1.5
BIO-SOFT® N91-3.25	C9-11 Alcohol ethoxylate	3.25	306	Liquid	9.1	99.5 min.	8.02	-12	<3 ¹	26.4	27.5	49.9	5	3.8	3.4
BIO-SOFT® N91-6	C9-11 Alcohol ethoxylate	6	425	Liquid	12.4	99.5 min.	8.25	6	53 ¹	27.2	34.5	52.5	7	13.5	10.5
BIO-SOFT® N91-8	C9-11 Alcohol ethoxylate	8	524	Liquid	13.9	99.5 min.	8.40	14	81 ¹	29.6	40.9	53.9	10	13	11
BIO-SOFT® N1-3	C11 Alcohol ethoxylate	3	305	Liquid	8.7	99.5 min.	7.75	-7	<0 ¹	26.0	26.3	41.3	19	3.2	3.1
BIO-SOFT® N1-5	C11 Alcohol ethoxylate	5	392	Liquid	11.2	99.5 min.	8.08	7	18 ¹	27.1	27.0	44.0	5	10	7
BIO-SOFT® N1-7	C11 Alcohol ethoxylate	7	479	Liquid	12.9	99.5 min.	7.75	12	58 ¹	28.0	28.7	44.8	7	12	9.5
BIO-SOFT® N1-9	C11 Alcohol ethoxylate	9	569	Liquid	13.9	99.5 min.	8.08	20	78 ¹	30.6	32.2	47.3	12	12.5	10.5
BIO-SOFT® N23-3	C12-13 Alcohol ethoxylate	3	322	Liquid	8.1	99.5 min.	7.70	4	<0 ¹	26.0	26.3	28.4	66	1.7	1.7
BIO-SOFT® N23-5	C12-13 Alcohol ethoxylate	5	413	Liquid	10.7	99.5 min.	8.00	11	<25 ¹	27.6	27.8	33.8	19	4.7	4.6
BIO-SOFT® N23-6.5	C12-13 Alcohol ethoxylate	6.5	484	Liquid	11.9	99.5 min.	8.16	16.7	43 ¹	27.8	27.7	32.3	9	11	10
BIO-SOFT® N25-3	C12-15 Alcohol ethoxylate	3	330	Liquid	8	99.5 min.	7.71	8	<0 ¹	26.1	26.4	29.3	123	1.5	1.4
BIO-SOFT® N25-7	C12-15 Alcohol ethoxylate	7	524	Slurry	12.2	99.5 min.	8.00	20	49 ¹	28.6	28.5	34.1	16	10.5	9.5
BIO-SOFT® EN8-90	C12-15 Alcohol ethoxylate	7.8	560	Liquid	13.3	90 min.	8.33	10	62 ¹	29.2	29.7	33.9	19	9.6	9.5
BIO-SOFT® E-678	C12-15 Alcohol ethoxylate	9	597	Liquid	13.3	85 min.	8.05	10	74 ¹	30.3	30.4	36.6	17	10.5	9.5
BIO-SOFT® N25-9	C12-15 Alcohol ethoxylate	9	597	Paste	13.3	99.5 min.	8.00	25	74 ¹	30.3	30.4	36.6	17	10.5	9.5
BIO-SOFT® N25-12	C12-15 Alcohol ethoxylate	12	761	Paste	14.4	99.5 min.	8.43	26	78 ²	34.5	34.7	35.6	58	10.7	9.9
BIO-SOFT® N45-7	C14-15 Alcohol ethoxylate	7	545	Liquid	11.6	100	8.07 @ 40°C	24	46 ¹	29.7	29.6	32.7	15	8.1	8.1
Lauryl Alcohol Ethoxylates															
BIO-SOFT® EC-600	C12-14 Alcohol ethoxylate	7	494	Liquid	12.2	99.5 min.	8.00	19	51 ¹	28.6	28.3	33.8	10	10.5	9.5
BIO-SOFT® EC-690	C12-14 Alcohol ethoxylate	7	494	Liquid	12.2	89.5 min.	8.23	5	51 ¹	28.7	28.1	34.9	14	11	9
BIO-SOFT® EC-639	C12-14 Alcohol ethoxylate	8	547	Liquid	13.3	90 min.	8.50	24	73 ¹	30.3	29.8	38.6	20	10.5	9
BIO-SOFT® AE-8	C12-14 Alcohol ethoxylate	8	555	Liquid	13	100	8.50	21	73 ¹	32.1	31.4	35.3	9	9.3	9.2
BIO-SOFT® AE-12	C12-14 Alcohol ethoxylate	12	727	Wax	14.7	100	8.70	65	97 ³	35.0	34.3	38.4	36	9.9	9.5
BIO-SOFT® E-840	C12-14 Alcohol ethoxylate	23	1209	Wax	16.9	99	9.10	41	78 ³	43.7	42.2	38.5	>300	10.8	8.8
BIO-SOFT® E-847	C12-14 Alcohol ethoxylate	23	1209	Liquid	16.9	74-76	7.10	17	77 ³	40.2	35.4	38.4	75	9	7.6
Alcohol Ethoxylates															
BIO-SOFT® DR-13	Alcohol ethoxylate	Proprietary	Proprietary	Liquid	13	100	8.26 @ 45°C	13	56 ¹	28.0	44.0	55.0	5.3	5.0	0.4
BIO-SOFT® DR-139	Alcohol ethoxylate	Proprietary	Proprietary	Liquid	13	90	8.49	-39	56 ¹	28.0	45.0	57.0	7.9	4.5	0.4

¹ 1% in water ³ 1% in 10% NaCl aqueous ⁵ 1% in 1% NaCl aqueous ⁷ 2% in 10% NaCl aqueous ⁹ 10% in water
² 1% in 5% NaCl aqueous ⁴ 2% in 33% Ethylene glycol monobutyl ether aqueous ⁶ 10% in 25% Diethylene glycol butyl ether ⁸ 5% in water ¹⁰ 5g in 25g BDG1 25%

Stepan Trade Name	Chemical Description	Average # of Moles EO	Molecular Weight	Appearance at 25°C	HLB	Activity, %	Density at 25°C, U.S. lbs/gal	Pour Point, °C	Cloud Point, °C	Surface Tension, dynes/cm			Draves Wetting Test, seconds	Ross Miles Foam Test, cm	
										% Deionized (DI) Water				0.1% in DI Water	
										0.10%	0.01%	0.001%		Initial	5 minutes
Branched Alcohol Ethoxylates															
MAKON® DA-4	Decyl alcohol ethoxylate	4	324	Liquid	10	99 min.	8.00	-13	<25 ¹	26.3	41.6	56.7	2	2.1	0.2
MAKON® DA-6	Decyl alcohol ethoxylate	6	431	Liquid	12	99 min.	8.20	6	43 ¹	26.6	42.4	56.3	5	12.5	1.5
MAKON® DA-9	Decyl alcohol ethoxylate	9	563	Liquid	14	99 min.	8.40	1	80 ¹	28.7	44.9	49.7	19	11.5	4.5
MAKON® UD-5	Undecyl alcohol ethoxylate	5	394	Liquid	10.9	99.5 min.	8.12	4	63 ¹⁰	26.8	33.8	50.4	3	5.5	3
MAKON® UD-6	Undecyl alcohol ethoxylate	6	438	Liquid	11.9	99.5 min.	8.22	9	69 ¹⁰	26.8	34.3	49.3	3	8.4	5.2
MAKON® UD-7	Undecyl alcohol ethoxylate	7	482	Liquid	12.8	99.5 min.	8.33	12	54 ¹	26.9	37.4	53.0	3	10	5.6
MAKON® UD-8	Undecyl alcohol ethoxylate	8	525	Liquid	13.2	99.5 min.	8.39	12	64 ¹	27.2	39.0	52.8	4	10	8.9
MAKON® TD-3	Tridecyl alcohol ethoxylate	3	333	Liquid	8	100	7.76	<-12	<25 ¹	27.2	26.9	38.6	13	1	0.3
MAKON® TD-6	Tridecyl alcohol ethoxylate	6	474	Liquid	11	99 min.	8.10	7	<25 ¹	27	27	35.3	12	4	4
BIO-SOFT® TD-630	Tridecyl alcohol ethoxylate	8	562	Liquid	12.3	95	8.01	7	47 ¹	27.5	27.7	37.3	4	9.5	5
MAKON® TD-9	Tridecyl alcohol ethoxylate	9	570	Liquid	13.1	99.5 min.	8.40	14	57 ¹	27.7	28.5	39.9	12	4	4
MAKON® TD-12	Tridecyl alcohol ethoxylate	12	724	Paste	14	100	8.35	17	89 ¹	31.2	31.9	39.1	20	10.9	9.9
MAKON® TD-18	Tridecyl alcohol ethoxylate	18	936	Solid	16	100	8.35	21	>100 ¹	32.7	34.2	50.1	26	11.6	10.3
MAKON® TD-189	Tridecyl alcohol ethoxylate	18	936	Liquid	16	90	8.51	21	>100 ¹	34.0	36.3	31.9	18	11.5	9.9
MAKON® TD-30	Tridecyl alcohol ethoxylate	30	1496	Solid	17.4	99.5 min.	8.82 @ 50°C	41	>100 ¹	41.1	48.4	38.0	>300	11.8	10.8
MAKON® XP-80	Propylheptanol alcohol ethoxylate	8	495	Liquid	13	100	8.42	11	55 ¹	28.0	46.1	56.5	5.1	5.0	0.4
Amide Ethoxylates															
NINOL® 1301	Amide ethoxylate	6	552	Solid	12.8	100	8.22	30	>100 ¹	30.3	30.7	32.2	50	1.8	1
NINOL® C-5	Amide ethoxylate	6	477	Liquid	14.6	100	8.30	12	87 ¹	31.6	32.3	33	24	10.3	9.9
NINOL® C-5 SPECIAL	Amide ethoxylate	6	477	Liquid	14.6	100	8.51	12	87 ¹	31.6	32.3	33	24	10.3	9.9
Tallowamine Ethoxylates															
BIO-SOFT® TA-2	Tallowamine ethoxylate	2	Proprietary	Liquid	5	100	7.40 (at 38 °C)	-10	<0 ¹	27.7	28.1	29.4	133	0.8	0.6
TOXIMUL® TA-5	Tallowamine ethoxylate	5	Proprietary	Liquid	9	100	7.90	15	32 ¹	31.7	31.7	37.4	22	5	4.7
TOXIMUL® TA-8	Tallowamine ethoxylate	8	Proprietary	Liquid	11	100	8.18	2	79 ¹	35.2	36.8	39.4	41	8.5	7.5
TOXIMUL® TA-10	Tallowamine ethoxylate	10	Proprietary	Liquid	11.7	99.5 min.	8.32	18	>100 ¹	37.1	38.7	39.2	70	9.1	8
TOXIMUL® TA-15	Tallowamine ethoxylate	15	Proprietary	Liquid	14	100	8.50	2	98 ²	40.4	41.4	48.5	>300	9.5	0.5
TOXIMUL® TA-20	Tallowamine ethoxylate	20	Proprietary	Liquid	16.5	99.5 min.	8.71	10	>100 ²	43.1	43.2	48.0	>300	7.7	2.3

¹ 1% in water ³ 1% in 10% NaCl aqueous ⁵ 1% in 1% NaCl aqueous ⁷ 2% in 10% NaCl aqueous ⁹ 10% in water
² 1% in 5% NaCl aqueous ⁴ 2% in 33% Ethylene glycol monobutyl ether aqueous ⁶ 10% in 25% Diethylene glycol butyl ether ⁸ 5% in water ¹⁰ 5g in 25g BDG1 25%

Stepan Trade Name	Chemical Description	Average # of Moles EO	Molecular Weight	Appearance at 25°C	HLB	Activity, %	Density at 25°C, U.S. lbs/gal	Pour Point, °C	Cloud Point, °C	Surface Tension, dynes/cm			Draves Wetting Test, seconds	Ross Miles Foam Test, cm	
										% Deionized (DI) Water				0.1% in DI Water	0.1% in DI Water
										0.10%	0.01%	0.001%	Initial		5 minutes
Cocoamine Ethoxylates															
TOXIMUL® CA-2	Cocoamine ethoxylate	2	294	Liquid	6	100	7.51	2	<0 ¹	27.8	27.8	45.3	44	1.8	1.6
TOXIMUL® CA-7.5	Cocoamine ethoxylate	7.5	529	Liquid	12	100	8.26	-18	99 ¹	35.0	34.9	49.6	90	10.7	7.9
Tall Oil Fatty Acid Ethoxylates															
NINEX® MT-603	Tall oil fatty acid ethoxylate	3	Proprietary	Liquid	6	100	8.40	<-1	40 ⁶	32.4	33.3	35.5	>300	1.1	1.0
NINEX® MT-610	Tall oil fatty acid ethoxylate	10	Proprietary	Liquid	12	99.6 min.	8.70	21	22.5 ⁵	37.0	38.6	52.3	>300	6.5	4
NINEX® MT-615	Tall oil fatty acid ethoxylate	15	Proprietary	Liquid	13	99.5 min.	8.80	13	53 ⁵	38.3	39.7	43.5	>300	5.2	3.7
NINEX® MT-630F	Tall oil fatty acid ethoxylate	30	Proprietary	Solid	16	99.5 min.	8.90 (at 40°C)	22	78 ⁵	41.9	43.2	47.2	>300	4.8	3.7
Polyarylphenol Alkoxylates/Ethoxylates															
MAKON® TSP-12	Tristyrylphenol ethoxylate	12	935	Liquid	12	99.5 min.	9.20	-8	27 ¹	41.1	41.6	43.6	104	4.9	3.1
MAKON® TSP-16	Tristyrylphenol ethoxylate	16	1049	Liquid	13	99.5 min.	9.30	19	62 ¹	42.1	42.1	36.8	43	4.5	0.6
MAKON® TSP-20	Tristyrylphenol ethoxylate	20	1282	Paste	14	99.5 min.	9.20	30	84 ¹	44.2	43.7	46.1	>300	7.2	2.9
MAKON® TSP-25	Tristyrylphenol ethoxylate	25	1496	Solid	15	99.5 min.	9.00	40	>94 ¹	46.1	46.0	40.0	>300	7.3	3.2
MAKON® TSP-25F	Tristyrylphenol alkoxylate	25	Proprietary	Liquid	14	100	9.24	8	55 ³	44.9	45.1	48.3	>300	7.9	5.1
MAKON® TSP-40N	Tristyrylphenol ethoxylate	40	2117	Solid	16	99.5 min.	9.10	35	>100 ¹	49.7	71.6	50.5	>300	6	2.4
MAKON® TSP-40F	Tristyrylphenol alkoxylate	40	Proprietary	Liquid	15	100	9.20	19	58.5 ³	47.3	47.8	50.2	>300	7.1	3.8
MAKON® TSP-54	Tristyrylphenol ethoxylate	54	2805	Solid	16	99.5 min.	9.10 (at 50°C)	37	>100 ¹	49.6	51.7	52.8	>300	7.7	4.7
MAKON® TSP-60	Tristyrylphenol ethoxylate	60	2877	Solid	18	99.5 min.	9.10	44	>100 ¹	50.3	52.0	52.1	>300	5.5	2.6
MAKON® TSP-60F	Tristyrylphenol alkoxylate	60	Proprietary	Paste	16	100	9.20	21	59 ³	47.9	48.3	52.8	>300	5.9	3.9
STEP-FLOW® 1500	Tristyrylphenol polyalkylene oxide block copolymer	Proprietary	Proprietary	Liquid	17	100	9.20	4	61 ¹	43.2	43.5	45.5	250	7.8	3.9
Nonylphenol Ethoxylates															
MAKON® 4	Nonyl phenol ethoxylate	4	398	Liquid	9	99.8	8.68	-20	<10 ¹	27.2	27.3	32.6	226	0.9	0.2
MAKON® 6	Nonyl phenol ethoxylate	6	480	Liquid	11	99.8	8.68	-29	<25 ¹	29.9	29.8	35.5	19	1.2	0.7
MAKON® 8	Nonyl phenol ethoxylate	8	591	Liquid	12	99.8	8.68	6	24 ¹	30.6	30.7	38.7	5	6.5	5
MAKON® 10	Nonyl phenol ethoxylate	10	638	Liquid	13	99.8	8.85	4	54 ¹	31.6	31.5	39.7	8.4	7.9	6.8
MAKON® 12	Nonyl phenol ethoxylate	12	747	Liquid	14	99.8	8.85	14	81 ¹	34.1	33.4	44.6	28.9	10.1	8.9
MAKON® 14	Nonyl phenol ethoxylate	14	843	Liquid	15	99.8	8.93	19	>100 ¹	36.8	36.3	48.1	39	9.9	9.2
MAKON® 30	Nonyl phenol ethoxylate	30	1435	Solid	17	99.5	8.93	40	>100 ¹	42.5	43.0	45.4	>300	11	9.6
MAKON® 40	Nonyl phenol ethoxylate	40	2040	Solid	17.8	99.5	8.93	44	>100 ¹	43.9	47.3	54.3	>300	9.9	9.3

¹ 1% in water ³ 1% in 10% NaCl aqueous ⁵ 1% in 1% NaCl aqueous ⁷ 2% in 10% NaCl aqueous ⁹ 10% in water
² 1% in 5% NaCl aqueous ⁴ 2% in 33% Ethylene glycol monobutyl ether aqueous ⁶ 10% in 25% Diethylene glycol butyl ether ⁸ 5% in water ¹⁰ 5g in 25g BDG1 25%

Stepan Trade Name	Chemical Description	Average # of Moles EO	Molecular Weight	Appearance at 25°C	HLB	Activity, %	Density at 25°C, U.S. lbs/gal	Pour Point, °C	Cloud Point, °C	Surface Tension, dynes/cm % Deionized (DI) Water			Draves Wetting Test, seconds 0.1% in DI Water	Ross Miles Foam Test, cm 0.1% in DI Water	
										0.10%	0.01%	0.001%		Initial	5 minutes
Octyl Phenol Ethoxylates															
MAKON® OP-3	Octyl phenol ethoxylate	3	326	Liquid	7.4	100	8.51	<-23	45 ⁷	Insoluble	Insoluble	Insoluble	Insoluble	Insoluble	Insoluble
MAKON® OP-9	Octyl phenol ethoxylate	9	602	Liquid	13.2	100	8.93	7	65 ¹	31.8	32.9	46.8	6	9.5	8.3
MAKON® OP-30	Octyl phenol ethoxylate	30	1275	Wax	17.3	99.5 min.	9.40 (at 50°C)	31	>100 ¹	28.4	31.9	48.8	29	9.2	9.1
MAKON® OP-3070	Octyl phenol ethoxylate	30	1275	Liquid	17.3	70	9.00	-9	66 ³	28.5	35.1	51.5	33	8.6	8.3
Castor Oil Ethoxylates															
TOXIMUL® 8243	Castor oil ethoxylate	20	Proprietary	Liquid	10	100	8.60	-12	<25 ¹	41.3	45.3	53.4	>300	3.5	1.3
STEPANTEX® CO-30	Castor oil ethoxylate	30	Proprietary	Liquid	12	100	8.80	6	62 ²	42.4	48.1	53	>300	4.5	3
STEPANTEX® CO-36	Castor oil ethoxylate	36	Proprietary	Liquid	13	100	8.80	13	75 ⁵	39.6	42.9	53.3	>300	4	3.5
STEPANTEX® CO-40	Castor oil ethoxylate	40	Proprietary	Liquid	13	100	8.90	16	85 ¹	39.5	40.8	51.8	>300	6	5
Sorbitan Ester Ethoxylates															
TOXIMUL® SEE-340	Sorbitan ester ethoxylate	20	Proprietary	Liquid	11	100	8.70	<-12	<25 ¹	38.0	46.5	57.5	>300	10	10
TOXIMUL® SEE-341	Sorbitan ester ethoxylate	20	Proprietary	Liquid	12	100	9.00	<-1	84 ¹	42.9	46.4	52.7	>300	4.6	4
Alcohol Alkoxylates															
MAKON® NF-12	Alcohol alkoxylate	Proprietary	Proprietary	Liquid	6	100	8.340	-10	15 ¹	32.7	33.8	36.6	9	0.25	0
MAKON® TD-50	Tridecyl alcohol alkoxylate	48	2478	Solid	16.4	99.5 min.	9.00	29	67 ⁴	39.1	52.3	44.1	>300	8.7	5.7
TOXIMUL® 8315	Butyl block copolymer	Proprietary	3500	Liquid	13	100	8.80	3	71 ¹	42.3	44.3	49.4	>300	3.2	0.6
TOXIMUL® 8320	Butyl block copolymer	Proprietary	5500	Liquid	12	100	8.80	20	50 ³	36.5	40.3	44.8	180	7.5	4.5
TOXIMUL® 8325	Butyl block copolymer	Proprietary	4000	Liquid	14	100	8.80	26	65 ¹	38.5	42.2	46.9	178	4.6	0.4
TOXIMUL® 8350	Butyl block copolymer	Proprietary	6200	Liquid	14	100	8.80	21	71 ⁹	35.7	38.3	45.4	42	8.1	6.1
Amide Alkoxylates															
MAKON® NF-5	Alkoxylated isopropyl amide	Proprietary	Proprietary	Liquid	5	97	8.50	4	-1 ¹	32.5	40.4	45.7	55	1.3	0.3

¹ 1% in water ³ 1% in 10% NaCl aqueous ⁵ 1% in 1% NaCl aqueous ⁷ 2% in 10% NaCl aqueous ⁹ 10% in water
² 1% in 5% NaCl aqueous ⁴ 2% in 33% Ethylene glycol monobutyl ether aqueous ⁶ 10% in 25% Diethylene glycol butyl ether ⁸ 5% in water ¹⁰ 5g in 25g BDG1 25%

Stepan Trade Name	Chemical Description	Average # of Moles EO	Molecular Weight	Appearance at 25°C	HLB	Activity, %	Density at 25°C, U.S. lbs/gal	Pour Point, °C	Cloud Point, °C	Surface Tension, dynes/cm % Deionized (DI) Water			Draves Wetting Test, seconds 0.1% in DI Water	Ross Miles Foam Test, cm 0.1% in DI Water	
										0.10%	0.01%	0.001%		Initial	5 minutes
EO/PO Block Copolymer Liquids															
<i>Note: MAKON® L-Series products contain <100 ppm ash catalyst. Upon request, an unfiltered grade denoted as "U" is available, containing approximately 1500 ppm ash.</i>															
MAKON® L61	Polyalkylene oxide block copolymer	Proprietary	2000	Liquid	3	100	8.46	-32	24 ¹	Insoluble	43.7	46.9	Insoluble	Insoluble	Insoluble
MAKON® L62	Polyalkylene oxide block copolymer	Proprietary	2500	Liquid	7	100	8.65	-41	32 ¹	42.3	44.6	48.6	>360	1.6	0.1
MAKON® L64	Polyalkylene oxide block copolymer	Proprietary	2900	Liquid	15	100	8.74	18	58 ¹	41.5	44.4	48.0	>360	1.3	0
TOXIMUL® 8321	Polyalkylene oxide block copolymer	Proprietary	3650	Liquid	7	100	8.60	2	16 ⁹	35.9	37.8	44.5	14	2	0.1
MAKON® L101	Polyalkylene oxide block copolymer	Proprietary	3800	Liquid	1	100	8.48	-36	15 ¹	Insoluble	34.8	39.2	Insoluble	Insoluble	Insoluble
STEP-FLOW® 26F	Polyalkylene oxide block copolymer	Proprietary	5900	Liquid	13	100	8.35	7	82 ¹	35.5	38.4	40.9	38	8.7	7.9
EO/PO Block Copolymer Pastes															
MAKON® P65/75	Polyalkylene oxide block copolymer	Proprietary	3800	Paste	17	100	8.53 (at 60°C)	27	82 ¹	41.8	45.0	47.9	>360	4.4	1.4
TOXIMUL® 8323	Polyalkylene oxide block copolymer	Proprietary	3800	Paste	15	100	8.68 (at 50°C)	27	82 ¹	41.8	45.0	47.9	>360	4.4	1.4
MAKON® P104	Polyalkylene oxide block copolymer	Proprietary	5900	Paste	13	100	8.46 (at 60°C)	32	82 ¹	35.7	38.9	42.9	>360	9.2	9.0
MAKON® P105*	Polyalkylene oxide block copolymer	Proprietary	6500	Paste	15	100	8.60 (at 60°C)	36	63 ³	35.7	38.5	42.9	>360	8.2	7.3
Reverse EO/PO Block Copolymer Liquids															
<i>Note: MAKON® R-Series products contain <100 ppm ash catalyst.</i>															
MAKON® 17R2	Polyalkylene oxide block copolymer	Proprietary	2150	Liquid	6	100	8.59	-39	35 ¹	43.0	45.8	48.8	>360	0	0
MAKON® 17R4	Polyalkylene oxide block copolymer	Proprietary	2650	Liquid	12	100	8.73	10	46 ⁸	45.2	48.1	51.1	69	0.2	0

*Samples available upon request. For commercial status of this product, please contact your Stepan Sales Representative.

¹ 1% in water ³ 1% in 10% NaCl aqueous ⁵ 1% in 1% NaCl aqueous ⁷ 2% in 10% NaCl aqueous ⁹ 10% in water
² 1% in 5% NaCl aqueous ⁴ 2% in 33% Ethylene glycol monobutyl ether aqueous ⁶ 10% in 25% Diethylene glycol butyl ether ⁸ 5% in water ¹⁰ 5g in 25g BDG1 25%

Stepan Trade Name	Chemical Description	Average # of Moles EO	Molecular Weight	Appearance at 25°C	HLB	Activity, %	Density at 25°C, U.S. lbs/gal	Pour Point, °C	Cloud Point, °C	Surface Tension, dynes/cm			Draves Wetting Test, seconds	Ross Miles Foam Test, cm	
										% Deionized (DI) Water				0.1% in DI Water	
										0.10%	0.01%	0.001%		Initial	5 minutes
Specialty Nonionics															
MAKON® NF-180	Polymer	Proprietary	2562	Liquid	-	100	8.51	-71	18.5 ¹	32.2	35.3	40.1	9.6	3.1	0
Nonionic Blends															
BIO-SOFT® N1-73B	C11 Alcohol ethoxylate	N/A	427	Liquid	11.6	100	8.09	6	38 ¹	27.5	28.3	37	3	9.6	9.5
BIO-SOFT® N-400	C9-11 Alcohol ethoxylate C12-13 alcohol ethoxylate	N/A	301	Liquid	8.8	100	7.79	-10	<25 ¹	26.6	26.9	45.7	9	5.3	4.7
BIO-SOFT® N-600	C12-13 Alcohol ethoxylate	N/A	410	Liquid	10.6	100	7.74	5	<25 ¹	27.4	27.4	27.2	15	4.5	4
BIO-SOFT® N-900	C9-11 Alcohol ethoxylate	N/A	484	Liquid	13	95	8.34	6	64 ¹	29.5	35.8	55.9	8	12	11
BIO-SOFT® N-901	C9-11 Alcohol ethoxylate C12-13 alcohol ethoxylate	N/A	437	Liquid	12	96	8.19	5	40 ¹	27	28.4	47.7	6	11.8	10.5
BIO-SOFT® N-905	C9-11 Alcohol ethoxylate C12-15 alcohol ethoxylate	N/A	462	Liquid	12	95	8.22	5	51 ¹	27.6	27.9	34.7	18	11.5	10.8
BIO-SOFT® N-1200	C9-11 Alcohol ethoxylate C12-15 alcohol ethoxylate	N/A	585	Liquid	13.5	95	8.41	18	80 ¹	31.2	32.3	38	18	11.4	10.6
STEPOSOL® DG	Nonionic/Cationic blend	N/A	Proprietary	Liquid	N/A	98 min.	8.86	-22	>100 ¹	27.8	33	52.6	18	12.5	11.3

¹ 1% in water ³ 1% in 10% NaCl aqueous ⁵ 1% in 1% NaCl aqueous ⁷ 2% in 10% NaCl aqueous ⁹ 10% in water
² 1% in 5% NaCl aqueous ⁴ 2% in 33% Ethylene glycol monobutyl ether aqueous ⁶ 10% in 25% Diethylene glycol butyl ether ⁸ 5% in water ¹⁰ 5g in 25g BDG1 25%

Visit www.stepan.com/alkoxylates for more information.

2019 © Stepan Company. All Rights Reserved.

BIO-SOFT®, CEDEPAL®, MAKON®, NINEX®, NINOL®, STEP-FLOW®, STEPANTEX®, STEPOSOL®, and TOXIMUL® are registered trademarks of Stepan Company.

The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents. STEPAN COMPANY MAKES NO PRODUCT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, OR ADEQUACY. Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, furnishing, use, or reliance upon information provided herein. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

May 2020