



Formulation

Name	ECONOMY LIQUID DISH DETERGENT USING BIO-SOFT® S-101	
No.	1267	
Description	This economy liquid dishwash formulation provides good cleaning and foaming performance in manual dishwash applications.	
Formulation	INGREDIENTS:	<u>% by Weight</u> <u>Functionality</u>
	Water	q.s. to 100 Carrier
	Sodium Hydroxide (Caustic Soda)	1.80 Neutralizer
	BIO-SOFT® S-101	6.75 Primary Surfactant
	STEOL® CS-230	18.10 Primary Surfactant
	AMMONYX® LMDO	3.00 Secondary Surfactant
	Citric Acid, 50% Solution	As Needed pH Modifier
	Sodium Chloride	1.00 Viscosity Builder
	Preservative, Dye, Fragrance, etc.	q.s.
	Total	100.00
Procedure	<ol style="list-style-type: none"> 1. Charge water and add sodium hydroxide while mixing. 2. Slowly add the BIO-SOFT® S-101 acid and mix until homogeneous. Note: This neutralization generates heat. Keep the temperature below 50 °C (122 °F) while neutralizing. 3. Check the pH, and if it is below 5, adjust with Sodium Hydroxide until it is above 5. 4. Once the pH is above 5, add the STEOL® CS-230 and mix until homogeneous. 5. Add the AMMONYX® LMDO and mix until homogeneous. Check the pH. 6. Use Citric Acid, 50% Solution or Sodium Hydroxide to adjust the pH to between 6.5 - 8.5. 7. Add preservative, dye, fragrance and other additives and mix until homogeneous. 8. Add the sodium chloride to increase the viscosity and mix until homogeneous. <p>NOTE: STEOL® CS-130 or STEOL® CS-330 may be used in place of STEOL® CS-230 without affecting the performance or stability of the formulation, but the typical viscosity range may be different. See the "External Comment" section for the alternate viscosity ranges.</p>	
Physical Properties	Appearance at 25 °C	Clear liquid
	pH, as is	6.5-8.5
	Viscosity at 25 °C, cps	500 - 800
	Density at 25 °C, lbs/U.S. gal	8.59
	Density at 40 °C, lbs/U.S. gal	8.47
Storage/Stability	Freeze/Thaw (3 cycles)	Pass
	6 weeks at 4 °C (39 °F)	Stable
	6 weeks at 25 °C (77 °F)	Stable
	6 weeks at 40 °C (104 °F)	Stable
Instructions for Use	<p>Squirt a small amount of detergent into sink and fill sink with warm/hot water. Alternately, squirt a small amount of detergent onto damp sponge or washcloth.</p> <p>The performance of this formulation is equal to or slightly better compared to two national consumer economy brand dish detergents.</p>	

External
Comment

If using STEOL® CS-130 instead of STEOL® CS-230, the viscosity range is 850 - 1,150 cps. Reducing the amount of sodium chloride will reduce this viscosity range. If using STEOL® CS-330 instead of STEOL® CS-230, the viscosity range is 400 - 700 cps.

Registered
Trademarks
of Stepan
Company

BIO-SOFT®
STEOL®
AMMONYX®

For
Additional
Assistance

For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe).
For ordering assistance, call our Account Service Department at 1-800-457-7673.

The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents. **STEPAN COMPANY MAKES NO PRODUCT WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, EXPRESS OR IMPLIED, AND NO OTHER WARRANTY OR GUARANTY, EXPRESS OR IMPLIED, IS MADE, INCLUDING AS TO INFORMATION REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, OR ADEQUACY.** Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party for any direct, indirect, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy, furnishing, use, or reliance upon information provided herein. The vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

Stepan 

Stepan Company
Northfield, Illinois 60093
Telephone (847) 446-7500

Revision Date: Publication Date: 07/30/2018 © 2018, Stepan Company. All rights reserved.