



Formulation

| | | |
|----------------------|---|-------------------------------------|
| Name | ULTRA FABRIC SOFTENER DISPERSION USING 15% SOLIDS STEPANTEX® VT-90 | |
| No. | 1130 | |
| Description | This 15%-solids fabric softener is for use in the rinse cycle of the wash load. It is non-yellowing and provides excellent softening and static control while maintaining the rewet properties of the fabric. | |
| Formulation | INGREDIENTS: | % by Weight Functionality |
| | Deionized Water | 82.53 Carrier |
| | STEPANTEX® VT-90 | 16.67 Softener |
| | Calcium Chloride (20% by wt. solution) | 0.75 Viscosity Adjuster |
| | Ucarcide 250M | q.s.* Preservative |
| | Dye, Fragrance, Preservative | q.s. Additives |
| | Total | 100.00 |
| Procedure | <p>1. Charge Deionized Water at 55°C/131°F or heat it up to this temperature in the vessel. Dye can be added at this time.</p> <p>2. While mixing, slowly add STEPANTEX® VT-90 (which has been previously heated to a temperature of 50°C/122°F) to the water and agitate for 10 minutes. The esterquat will disperse into a thick cream-like consistency.</p> <p>3. Add Calcium Chloride solution to reduce viscosity and stabilize the system. Continue mixing for another 20 minutes.</p> <p>4. When the temperature has reached 35°C/95°F, charge Preservative and any other ingredients (e.g. Fragrance, optical brightener, etc.).</p> <p>* Use amount recommended by supplier.</p> | |
| Physical Properties | Appearance at 25°C/77°F | Opaque liquid |
| | pH, as is | 3.0 |
| | Viscosity at 25°C/77°F, cPs (Brookfield DV-II+ Pro) | Water-like |
| | Solids, % | 15.0 |
| | Density, Lb/gal | 8.34 |
| Storage/Stability | 4 weeks at 5°C/41°F | Stable |
| | 4 weeks at 40°C/104°F | Stable |
| | 4 weeks at 50°C/122°F | Stable |
| Instructions for Use | Use 1 oz. in rinse cycle for a regular wash load (4–6 lbs). | |
| External Comment | <p>For a more viscous product, the calcium chloride amount can be reduced. Final viscosity may vary, depending on the processing temperature, mixing rate, and time. Fragrance and other ingredients may also affect this parameter. Sodium chloride can also be used to adjust viscosity. Monitoring viscosity of the final fabric softener product at the storage temperature requirements is recommended.; Marketing Notes: STEPANATEX® VT-90 is an approved ingredient on</p> | |

www.cleangredients.org. For further information, visit our website or www.cleangredients.org. BCI = 81. Total BCI (Biorenewable Carbon Index) was calculated only for the Stepan surfactants used in this formulation.

Registered
Trademarks
of Stepan
Company

STEPANTEX®

For
Additional
Assistance

For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe).
For ordering assistance, call our Account Service Department at 1-800-457-7673.

Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

Stepan 

Stepan Company
Northfield, Illinois 60093
Telephone (847) 446-7500

Revision Date: Publication Date: 08/18/2010 © 2010, Stepan Company. All rights reserved.