



Formulation

Name	INDUSTRIAL SOLVENT METAL CLEANER	
No.	1207	
Description	This solvent-based degreaser quickly and easily removes motor oil, grease, and adhesive residue from metal surfaces.	
Formulation	INGREDIENTS:	<u>% by Weight</u> <u>Functionality</u>
	STEPOSOL® SC	45.0 Solvent
	STEPOSOL® DG	10.0 Primary Surfactant
	STEPOSOL® MET-10U	45.0 Surfactant/Solvent
	Total	100.0
Procedure	<ol style="list-style-type: none"> 1. Charge STEPOSOL® SC to mixing vessel. 2. With good agitation, slowly blend in STEPOSOL® DG. 3. When blended, add STEPOSOL® MET-10U. 4. Mix until homogenous. 	
Physical Properties	Appearance at 25°C	Clear liquid
	pH, as is	4.5
	Viscosity at 25°C, cps	Water thin
	VOC (calculated), %	25
Storage/Stability	Freeze/thaw, 3 cycles	Pass
	4 weeks at 50°C	Pass
	4 weeks at 4°C	Pass
	4 weeks at 25°C	Pass
Instructions for Use	Use as is. Apply to surface and then wipe with a clean cloth. For more heavily soiled metals, allow solution to penetrate for 10 minutes.	
External Comment	<p>Marketing Notes: Please refer to the Safety Data Sheet for global regulatory information. It is the responsibility of the end user to review the chemical control regulations for each country. BCI = 82. Total BCI (Biorenewable Carbon Index) was calculated only for the Stepan surfactants used in this formulation. For further information on Stepan's BCI, visit www.stepan.com. This formulation does not meet the California Air Resource Board (CARB) VOC regulation for Consumer Products. "Consumer" is defined by CARB as any person who seeks, purchases, or acquires any consumer product for personal, family, household, or institutional use. For U.S. formulators, STEPOSOL® MET-10U is a low vapor pressure VOC (LVP-VOC), therefore its contribution to the VOC calculation is zero. STEPOSOL® MET-10U does not contribute to the VOC calculation because of its high boiling point and low vapor pressure. Before using on plastic, hard or painted surfaces, spot test on an inconspicuous area first.</p>	
Registered Trademarks of Stepan Company	STEPOSOL®	

For
Additional
Assistance

For applications or product handling assistance, call our Technical Service Department at 1-800-745-7837 (U.S.) or 011-334-76-505-100 (Europe).

For ordering assistance, call our Account Service Department at 1-800-457-7673.

Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.



Stepan Company
Northfield, Illinois 60093
Telephone (847) 446-7500

Revision Date: Publication Date: 03/18/2014 © 2014, Stepan Company. All rights reserved.