



Environmentally-Friendly Solvents

Typical Properties

Stepan Trade Name	Base Material	Chemical Description	CAS #	Appearance @ 25°C	Viscosity @ 25°C, cps	Color		Density @ 25°C, U.S. lbs/gal	Specific Gravity
						APHA	Gardner		
STEPOSOL® C-25	Coconut oil	Methyl caprylate/caprates	68937-83-7	Clear liquid	2	11	1	7.3	0.870
STEPOSOL® C-42	Coconut oil	Methyl laurate/Methyl myristate	111-82-0, 124-10-7	Clear liquid	7	9	1	7.3	0.870
STEPOSOL® C-48	Coconut oil	Methyl laurate	61788-59-8	Clear liquid	11	32	1	7.2	0.860
STEPOSOL® C-65	Coconut oil	Methyl palmitate/oleate	67762-38-3	Clear liquid	7	28	1	7.2	0.860
STEPOSOL® M-8-10	Coconut oil	N,N-Dimethylcaprylamide, N,N-Dimethylcapramide	1118-92-9, 14433-76-2	Clear liquid	11	8	1	7.3	0.881
STEPOSOL® M-10	Coconut oil	N,N-Dimethylcapramide	14433-76-2	Clear liquid	9	37	1	7.3	0.878
STEPOSOL® ROE-W	Canola oil	Canola methyl ester	67762-38-3	Clear liquid	10	239	2	7.3	0.876
STEPOSOL® SB-D	Soybean oil	Soya methyl ester	67784-80-9	Clear liquid	15	58	1	7.3	0.877
STEPOSOL® SB-W	Soybean oil	Soya methyl ester	67784-80-9	Clear liquid	7	320	1	7.3	0.877
STEPOSOL® SC	Soybean/corn oil	Soya methyl ester/Ethyl lactate	67784-80-9, 97-64-3	Clear liquid	10	225	1	7.9	0.946

For more information or to request a sample, contact Stepan's Technical Service Department at 1-800-745-7837 (STEP) or techserv@stepan.com.

Publication Date: February 2011

Page 1 of 4

STEPOSOL® is a registered trademark of Stepan Company.

Disclaimer:

Nothing contained herein grants or extends a license, expressed or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness adequacy or furnishing of such information.

© 2010. Stepan Company. All rights reserved.



Environmentally-Friendly Solvents

Typical Properties

Stepan Trade Name	Flash Point (PMCC)		Boiling Point @ 760mm HG		Cloud Point		Pour Point		Melting Point		Freeze Point	
	°C	°F	°C	°F	°C	°F	°C	°F	°C	°F	°C	°F
STEPOSOL® C-25	78	173	200	392	-35.4	-31.7	-37.0	-34.6	-42.1	-43.7	-49.3	-56.7
STEPOSOL® C-42	>94	>201	274	525	-3.8	25.2	-4.0	24.8	-5.0	23.0	-9.4	15.0
STEPOSOL® C-48	>94	>201	276	529	-1.7	28.9	-2.4	27.7	-2.8	26.8	-6.0	21.2
STEPOSOL® C-65	>94	>201	305	581	15.6	60.1	14.3	57.7	14.0	57.2	10.0	50.0
STEPOSOL® M-8-10	118	245	260	500	<-20.0	<-4.0	-19.6	-3.3	-17.0	1.4	-34.0	-29.2
STEPOSOL® M-10	120	248	278	532	<-14.0	<6.8	-14.0	6.8	-2.5	27.5	-17.0	1.4
STEPOSOL® ROE-W	>94	>201	361	682	-2.3	27.9	-13.8	7.2	-10.9	12.5	-24.5	-12.1
STEPOSOL® SB-D	>94	>201	341	646	-2.1	28.2	-2.7	27.1	-0.6	30.9	-7.7	18.1
STEPOSOL® SB-W	>94	>201	352	665	-1.1	30.0	-1.6	29.1	0.1	32.1	-5.7	21.7
STEPOSOL® SC	69	156	163	325	-2.7	27.1	-6.0	21.2	-4.7	23.6	-15.1	4.8

For more information or to request a sample, contact Stepan's Technical Service Department at 1-800-745-7837 (STEP) or techserv@stepan.com.

Page 2 of 4

STEPOSOL® is a registered trademark of Stepan Company.

Disclaimer:

Nothing contained herein grants or extends a license, expressed or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness adequacy or furnishing of such information.

© 2010. Stepan Company. All rights reserved.



Environmentally-Friendly Solvents

Typical Properties

Stepan Trade Name	Refractive Index @ 20°C	Surface Tension (neat), dynes/cm	Solubility			
			Water	Methanol	Kerosene	Xylene
STEPOSOL® C-25	1.420	27.7	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® C-42	1.430	29.4	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® C-48	1.437	29.6	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® C-65	1.445	30.8	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® M-8-10	1.452	30.9	Partially soluble	Soluble	Soluble	Soluble
STEPOSOL® M-10	1.453	31.1	Partially soluble	Soluble	Soluble	Soluble
STEPOSOL® ROE-W	1.456	31.4	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® SB-D	1.458	31.5	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® SB-W	1.457	31.5	Insoluble	Soluble	Soluble	Soluble
STEPOSOL® SC	1.435	30.1	Insoluble	Soluble	Soluble	Soluble

For more information or to request a sample, contact Stepan's Technical Service Department at 1-800-745-7837 (STEP) or techserv@stepan.com.

Page 3 of 4

STEPOSOL® is a registered trademark of Stepan Company.

Disclaimer:

Nothing contained herein grants or extends a license, expressed or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness adequacy or furnishing of such information.

© 2010. Stepan Company. All rights reserved.



Environmentally-Friendly Solvents

Typical Properties

Stepan Trade Name	Kauri-Butanol Value	VOC% (CARB 310)	LVP-VOC	HAP	BCI*	Biodegradability
STEPOSOL® C-25	112	89	N	N	90	B
STEPOSOL® C-42	112	13	Y	N	93	B
STEPOSOL® C-48	75	25	Y	N	93	B
STEPOSOL® C-65	68	0.5	Y	N	94	B
STEPOSOL® M-8-10	>300	33	Y	N	82	R
STEPOSOL® M-10	>300	15	Y	N	83	R
STEPOSOL® ROE-W	55	0.60	Y	N	95	B
STEPOSOL® SB-D	59	0.03	Y	N	93	B
STEPOSOL® SB-W	38	0.50	Y	N	95	B
STEPOSOL® SC	318	50.02	N	N	98	B

VOC% (CARB 310) refers to California Air Resources Board Method 310 for VOC determination.

LVP-VOC: Low vapor pressure VOC. California's OTC Model Rule and National VOC Standards exempt LVP-VOC from VOC limit requirements.

HAP: Hazardous Air Pollutant as listed by U.S.EPA under the 1990 Clean Air Act.

***BCI (Biorenewable Carbon Index):** Number of natural carbons (plant, animal or marine based) divided by the total number of carbons, multiplied by 100.

B indicates that the product is biodegradable; contact Stepan Company for more information.

R indicates that the product is readily biodegradable, where 60%-70% of the substance biodegrades to carbon dioxide and water in 28 days and meets the 10-day window.

For more information or to request a sample, contact Stepan's Technical Service Department at 1-800-745-7837 (STEP) or techserv@stepan.com.

STEPOSOL® is a registered trademark of Stepan Company.

Disclaimer:

Nothing contained herein grants or extends a license, expressed or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the work of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness adequacy or furnishing of such information.