



Product Name	<b>STEPCOTE™ W-811</b>
Chemical Description	Alcohol phosphate
Application	<p>STEPCOTE W-811 is an effective wetting agent for use in waterborne coatings. It can be incorporated during the letdown phase of production or post added to the final formulation. Typical use level, based on active content, is 2 – 6 lbs/100 gallons, however, optimal dosing should be determined by performing a ladder study. STEPCOTE W-811, although primarily a wetting agent, may positively impact the following coatings properties:</p> <ul style="list-style-type: none"><li>• Gloss</li><li>• Color Acceptance</li><li>• Wet Scrub Resistance</li><li>• Hiding</li></ul>
Typical Properties	<p>Appearance at 25 °C..... Clear liquid Actives, % ..... 100 Density at 25°C, g/mL (lbs/U.S. gal) ..... 1.07 (8.9) pH, 1% aqueous at 25 °C ..... 6 Flash Point, TAG, °C (°F)..... 138 (280)</p>
Storage & Handling	<p><u>Standard Packaging:</u> STEPCOTE W-811 is available in bulk quantities.</p> <p>STEPCOTE W-811 should be stored in a cool, dry place in closed containers.</p> <p>Normal safety precautions (i.e., gloves and safety goggles) should be employed when handling STEPCOTE W-811. Contact with eyes, nose and skin should be avoided.</p>
Clearances	<p>The international inventories (country clearances) of STEPCOTE W-811 can be found in Section 15 of the Safety Data Sheet (SDS). <b>It is the responsibility of the formulator to review the chemical control regulations for each country where the end product is intended to be sold or used.</b> If you have any further questions regarding inventories, please contact North American Technical Service at <a href="mailto:techserv@stepan.com">techserv@stepan.com</a>.</p>



Product  
Stewardship


Additional  
Safety  
Information

This product bulletin has been written in accordance with ACC's Product Stewardship guidelines.

A Safety Data Sheet is available upon request.



The information contained herein is based on the manufacturer's own study and the works of others and is subject to change without prior notice. The information is not intended to be all-inclusive, including as to the manner and conditions of use, handling, storage or disposal or other factors that may involve additional legal, environmental, safety or performance considerations. Nothing contained herein grants or extends a license, express or implied, in connection with any patents issued or pending of the manufacturer or others, or shall be construed as a recommendation to infringe any patents or to violate any applicable laws. **STEPAN COMPANY MAKES NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR USE, AND NO WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE, INCLUDING REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY, ACCURACY, COMPLETENESS, ADEQUACY OR OTHERWISE.** Stepan Company (and its employees, subsidiaries and affiliates) shall not be liable (regardless of fault) to the vendee, its employees, or any other party in respect of this information, including in respect of its accuracy, completeness, adequacy, furnishing, use, or reliance upon, and the vendee assumes and releases Stepan Company (and its employees, subsidiaries and affiliates) from all liability, whether in tort, contract or otherwise to the fullest extent possible under the relevant law.

**Stepan**   
**Corporate Headquarters**  
**Northfield, Illinois 60093, U.S.A.**  
**Phone: 847-446-7500**  
**Fax: 874-501-2100**  
**Website: [www.stepan.com](http://www.stepan.com)**

For Technical Service Call:  
Stepan North America **+1-800-745-7837**  
Stepan Mexico **+55-11-5089-2208**  
Stepan Quimica **+55-11-5089-2200**  
Stepan Colombia **+571-636-2808**  
Stepan Europe **+33-476-505-160**  
Stepan Asia **+656-879-9855**  
Stepan Philippines **+656-879-9855**

For Customer Service Call:  
Stepan North America **+1-800-457-7673**  
Stepan Mexico **+52-555-533-1967**  
Stepan Quimica **+55-11-5089-2200**  
Stepan Colombia **+57-6-8993125**  
Stepan UK **+44-161-338-5511**  
Stepan France **+33-476-50-51-00**  
Stepan Philippines **+63-2-842-7951**