



Product Name	TOXIMUL[®] 3473F, 3474F, 3476F, and 3479F		
Chemical Description	TOXIMUL 3470F series surfactants are blends of linear calcium sulfonate and non-alkylphenol nonionic surfactants.		
Applications	TOXIMUL 3470F series surfactants are general agricultural emulsifiers. They are used in combination with each other, generally in pairs, in an extensive range of pesticide formulations.		
Typical Properties	<u>TOXIMUL 3473F</u>	<u>TOXIMUL 3474F</u>	
	Appearance at 25°C.....	Dark Amber Liquid	Dark Amber Liquid
	Density, g/ml (lbs/U.S. gal) at 25°C.....	1.02 (8.5)	1.03 (8.6)
	Moisture, %.....	1.0 max	1.0 max
	pH, 5% in 1:1 IPA/H ₂ O.....	5.7	5.4
	Viscosity, cps, at 25°C.....	325	6160
	Flash Point, SETA, °C (°F).....	69.4 (157)	63.9 (147)
	Pour Point, °C (°F).....	8 (46)	-23 (<10)
	HLB.....	10	6
	RVOC, U.S. EPA, %.....	25	28
	Solubility: Water.....	Dispersible	Dispersible
	Methanol.....	Soluble	Dispersible
	Kerosene.....	Insoluble	Soluble
	Xylene.....	Soluble	Soluble
	<u>TOXIMUL 3476F</u>	<u>TOXIMUL 3479F</u>	
	Appearance at 25°C.....	Dark Amber Liquid	Dark Amber Liquid
	Density, g/ml (lbs/U.S. gal) at 25°C.....	1.04 (8.7)	1.01 (8.5)
	Moisture, %.....	1.0 max	1.0 max
	pH, 5% in 1:1 IPA/H ₂ O.....	5.4	5.8
	Viscosity, cps, at 25°C.....	3990	630
	Flash Point, SETA °C (°F).....	69.4 (157)	67.8 (154)
	Pour Point, °C (°F).....	-23 (10)	9 (48)
	HLB.....	8	13
	RVOC, U.S. EPA, %.....	24	25
	Solubility: Water.....	Dispersible	Dispersible
	Methanol.....	Dispersible	Soluble
	Kerosene.....	Insoluble	Insoluble
	Xylene.....	Soluble	Soluble
Other Data	U.S. DOT Classification.....	Combustible	Combustible
Storage & Handling	Normal safety precautions (i.e. gloves and safety goggles) should be employed when handling TOXIMUL 3470 series. Contact with the eyes and prolonged contact with the skin should be avoided. Wash thoroughly after handling material. Use in a well ventilated area away from sparks and open flame.		

TOXIMUL[®] is a registered trademark of Stepan Company.



Storage & Handling

Bulk Storage Information: TOXIMUL 3473F, 3474F, 3476F, and 3479F stored in drums at temperatures below 55°F (13°C) may thicken or solidify. They may be fluidized by warming with a drum heater or in a steam room. Drums should be vented prior to heating to avoid excessive pressure build up. Product storage temperatures over 100°F (38°C) are not recommended as excessive solvent loss may occur. The flash point may be exceeded when warming to pump but the temperature should be below the flash point for storage.

Standard Packaging: TOXIMUL 3473F, 3474F, 3476F and 3479F are available in drums (450 lb, 205 kg) and in bulk quantities.

Clearances

All components of TOXIMUL 3470F series surfactants are approved for use in the following countries: United States (TSCA), Europe (EINECS/Polymer Exempt), Canada (DSL), Australia (AICS), Philippines (PICCS), China (IECSC), New Zealand (NZIoC), and Korea (ECL).

The TOXIMUL 3470F series are approved for use as inert ingredients under U.S. EPA 40 CFR 180.910 and 180.960, pre- and post-harvest applications.

Additional Safety Information

A Material Safety Data Sheet is available upon request.

Nothing contained herein grants or extends a license, express or implied, in connection with patents, issued or pending, of the manufacturer or others. The information contained herein is based on the manufacturer's own study and the works of others. The manufacturer makes no warranties, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. The manufacturer shall not be liable (regardless of fault) to the vendee's employees, or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

Stepan

Corporate Headquarters
Northfield, Illinois 60093, U.S.A.
847-446-7500 847-501-2100 fax
Website: www.stepan.com

For Technical Service Call: Northfield, IL USA 800-745-7837
Longford Mills, Canada 705-326-7329 • Mexico City, Mexico +52-555-533-1697
Voreppe, France +33-476-505-100 • Bogota, Colombia +57-1-6362808
Stalybridge, United Kingdom +44-141-338-9083
Manila, Philippines +632-891-1708

